

FLUKE.

Clamp meter, Type: 325**Order data**

Order number	473290 325
GTIN	095969623766
Item class	47H

Description**Version:**

Current clamps with large easy-to-read LCD display in a slim and ergonomic design. Backlit display.

Standard:

EN 61010-1

Supplied with:

Incl. test leads and padded carrying case. Batteries 2 pcs. No. 081561 size LR3.

Calibration: I4

Information displayed: 4000

Basic accuracy: 2 %

Continuity testing: $\leq 30 \Omega$

Measurement process: TRUE RMS (AC)

Memory function: HOLD, MAX/MIN

AC voltage: 0.1 V – 600 V

Technical description

AC voltage	0.1 V – 600 V
------------	---------------

Overvoltage category	CAT III 600 V
Overvoltage category	CAT IV 300 V
maximum jaw aperture	30 mm
Capacitance	100.0 μ F up to 1000 μ F
DC voltage	0.1 V – 600 V
Measurement process	TRUE RMS (AC)
DC current	0.1 A - 400 A
Continuity testing	$\leq 30 \Omega$
Frequency	5 Hz – 500 Hz
Information displayed	4000
AC current	0.1 A - 400 A
Memory function	HOLD, MAX/MIN
Basic accuracy	2 %
Resistance	0.1 Ω – 40 k Ω
Contact measurement of temperature	-10 - 400 $^{\circ}$ C
Article no of the battery / rechargeable battery fitted	081561 LR3
Number of batteries contained	2
Power supply	Battery-powered
Power supply	2x 081561 LR3
Calibration	I4
Type of product	Current clamp

Services

Calibration Current clamp Type D	017720 D
DAkkS calibration Current clamp Type D	016790 D
DAkkS calibration Clamp meter Type D	027060 D
Calibration Clamp meter Type D	027050 D

Accessories

Alkaline-manganese batteries International size LR3	081556 LR3
Alkaline-manganese batteries International size LR3	081561 LR3