

**BENNING****Digital current clamp, Manufacturer's designation: CM1-2****Order data**

Order number	473305 CM1-2
GTIN	4014650440624
Item class	47A

**Description****Version:**

Sturdy plastic casing with large-format, 4 inch and 3 1/2 inch LCD display.  
Reliable AC and DC measurements without breaking the operating circuit. Collection of measured value and maximum value, relative measurement.

**Application:**

Digital service multimeters for a wide range of applications. These provide a high level of safety and other additional functions.

**Standard:**

**IEC / EN 061010-1 (DIN VDE 0411-1).**

**Supplied with:**

Batteries, probe leads, compact protective case, operating instructions.

Calibration: I4

Information displayed: 2000

Basic accuracy: 1 %

acoustic continuity test: 0 – 20  $\Omega$

Measurement process: RMS

Memory function: 5

AC voltage: 0.1 V – 600 V

**Technical description**

AC current	0.1 A – 400 A
Basic accuracy	1 %
maximum jaw aperture	30 mm
DC voltage	0.1 V – 600 V
Resistance	0.1 $\Omega$ – 20 M $\Omega$
Overvoltage category	5
AC voltage	0.1 V – 600 V
Measurement process	RMS
Memory function	5
Manufacturer's designation	CM1-2
acoustic continuity test	0 – 20 $\Omega$
Information displayed	2000
Article no of the battery / rechargeable battery fitted	081561 LR3
Number of batteries contained	2
Power supply	Battery-powered
Power supply	2× 081561 LR3
Calibration	I4
Type of product	Current clamp

## Services

Calibration Current clamp Type D	017720 D
Labelling laser-etched Type	018940
DAkkS calibration Current clamp Type D	016790 D
DAkkS calibration Clamp meter Type D	027060 D
Calibration Clamp meter Type D	027050 D

## Accessories

Alkaline-manganese batteries International size LR3	081561 LR3
---	------------

Test leads Measuring tips Ø 4 mm	473308 4
Alkaline-manganese batteries International size LR3	081556 LR3
Test leads Measuring tips Ø 2 mm	473308 2