



## Multimeter, Type: 760-1



### Order data

Order number	473310 760-1
GTIN	4029547013942
Item class	47B

### Description

#### Version:

Sturdy plastic casing with large illuminated LCD display and rubberised gripping area.

**Automatic detection of the units of measurement, based on the socket assignment.**

**Automatic setting of the measurement range and type of measurement (AC/DC). Simple error-avoiding operation with illuminated function keys.**

#### Function:

IP64: Protected against splashed water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

#### Application:

Suitable for a wide range of field of application in electrical technology, industrial systems, maintenance, servicing (troubleshooting),

#### Standard:

**DIN EN 61326-1, EN 61010-2-033**

#### Supplied with:

3 batteries No. 081561 size LR3 and measurement leads.

IP Index of Protection: IP 64

Calibration: I3

Information displayed: 4000

Basic accuracy: 0.8 %

Continuity testing: yes

Diode testing: yes  
 AC voltage: 0.1 mV – 600 V  
 DC voltage: 0.1 mV – 600 V

## Technical description

DC voltage	0.1 mV – 600 V
DC current	1 mA - 10 A
Diode testing	yes
Overvoltage category	CAT IV 300 V; CAT III 600 V
Resistance	0.1 - 40 MΩ
Frequency	0.001 Hz - 512 kHz
Capacitance	0.001 nF - 100 μF
IP Index of Protection	IP 64
Continuity testing	yes
Basic accuracy	0.8 %
AC voltage	0.1 mV – 600 V
AC current	1 mA - 10 A
Calibration	I3
Information displayed	4000
Number of batteries contained	3
Article no of the battery / rechargeable battery fitted	081561 LR3
Power supply	Battery-powered
Type of product	Multimeter

## Services

Calibration Digital multimeter Number of decimal places 3	017710 3
Labelling laser-etched Type	018940
DAkkS calibration Digital multimeter Number of decimal places 3	016780 3

## Accessories

Alkaline-manganese batteries International size LR3	081556 LR3
Alkaline-manganese batteries International size LR3	081561 LR3