ALLURIS

FMI-B30 Digital precision force gauge (USB), Measuring range: 500 N



Order data

| Order number | 478985 500 |
|--------------|---------------|
| GTIN | 4260244680628 |
| Item class | 47F |

Description

Version:

- Sturdy force gauges in a handy aluminium die-cast housing for compressive and tensile forces from 0.001 to 2500 N.
- · Overload protection up to 500% and protected measurement shaft.
- · Attachment thread for additional handles.
- · Precise positioning in test stands by a guide pin.
- High measurement rate for precise recording of peak values to determine fracture or tearing forces.
- · Measured value memory with statistical analysis and limit value monitoring.
- USB interface for data transmission to a PC.

Advantage:

Measurement data software for evaluation in MsExcel. COM-Bridge software for direct data transmission from the measuring device to the Windows PC.

Operating time up to 150 h without mains power thanks to the rechargeable LiPo battery.

Function:

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

Application:

Measurement of compressive and tensile forces in quality assessment and production. For use as a mobile manual measurement gauge both in outdoor areas and in test stands or jigs.



Attachment thread integrated into the housing permit attachment in test stands or mounting of additional handles.

Supplied with:

Force gauge in a protective case. Screw-on accessories for force transfer (flat head, slot head, cone, hook). Quick-start instructions.

Software FMI-Connect. Calibration: Price on request IP Index of Protection: IP 65

Resolution: 0.1 N

Error limit: ±0.15 maximum value (±1 digit) %

Connection thread: M6

Length: 150 mm Width: 82 mm Height: 29 mm

Technical description

| IP Index of Protection | IP 65 |
|--|--|
| Measuring range | 500 N |
| Resolution | 0.1 N |
| Width | 82 mm |
| Length | 150 mm |
| Height | 29 mm |
| Error limit | ±0.15 maximum value (±1 digit) % |
| Connection thread | M6 |
| Type of rechargeable battery | Lithium-ion |
| Number of rechargeable batteries contained | 1 |
| Power supply | Rechargeable battery-powered |
| Interface | USB interface |
| Measurement technology | digital |
| Calibration | Price on request |
| Type of product | Draw bar pulling force gauge for tension and compression |
| | |



Accessories

479020