

## Setting ring DIN 2250 C, Nominal size $\varnothing$ : 115 mm



### Order data

|              |               |
|--------------|---------------|
| Order number | 484030 115    |
| GTIN         | 2050001952929 |
| Item class   | 48B           |

### Description

**Version:**

**Setting rings** (checking rings) of first class gauge steel, hardened, stress-relieved, ground and lapped. **Each setting ring is engraved with the actual size.** Manufacturer's tolerance for the bore is JS4.

**Application:**

For general applications, e.g. for setting and testing measuring tools.

**Standard:**

Nach **DIN 2250 C.**

**Note:**

Further intermediate sizes available on request or can simply be ordered at [www.hoffmann-group.com](http://www.hoffmann-group.com), for instance No. 484030 size 82.

Calibration: L7

Nominal size: 115 mm

### Technical description

|                |        |
|----------------|--------|
| Nominal size   | 115 mm |
| Tolerance zone | JS     |

|                                     |              |
|-------------------------------------|--------------|
| Standard                            | DIN 2250 C   |
| Manufacturing tolerance of the bore | JS4          |
| Material                            | Gauge steel  |
| Quality                             | 4            |
| Calibration                         | L7           |
| Type of product                     | setting ring |

### Services

|   |            |
|---|------------|
| Calibration Setting ring maximum Ø 500 mm       | 018430 500 |
| Labelling laser-etched Type                     | 018940     |
| DAkkS calibration Setting ring maximum Ø 200 mm | 019660 200 |
| DAkkS calibration Setting ring maximum Ø 200 mm | 028470 200 |
| Calibration Setting ring maximum Ø 500 mm       | 028400 500 |