

Threads "Go" / "No Go" plug gauge, TiN, Thread: M10



Order data

| | |
|--------------|---------------|
| Order number | 486008 M10 |
| GTIN | 2050001060464 |
| Item class | 48B |

Description

Version:

The ground first thread pitch removes coarse swarf in the component and prevents premature fracture of the first thread pitch. Version to DIN 2279 - 2299.

"Go" and "No Go" ends on a single handle (DIN 2240, part 1, form R). "No Go" end marked red.

"Go" end TiN coated, resulting in longer working life, dirt trap groove from M6.

Application:

For metric ISO threads, right-hand DIN 13.

Tolerance class 6H (up to M 1.4 = 5H).

Standard:

Toleranzen und Abmaße nach **DIN ISO 1502**.

Note:

Thread gauges for threads with other pitches, Whitworth, trapezoidal, round, UNC, UNF, NPT, and LH threads available on request.

Calibration: L10

Standard: DIN 13

Thread type: M

Thread pitch: 1.5 mm

Technical description

| | |
|-----------------|--------|
| Thread pitch | 1.5 mm |
| Tolerance class | 6H |
| Thread | M10 |
| Thread type | M |
| Standard | DIN 13 |

| | |
|-------------------|-----------------------------|
| Tolerance zone | H |
| Quality | 6 |
| Type of gauge | "No Go" gauge |
| Type of gauge | "Go" plug gauge |
| Surface "OK" side | TiN |
| Calibration | L10 |
| Type of product | Thread Go / NoGo plug gauge |

Services

| | |
|--|-----------|
| Calibration Go / No Go thread plug gauge maximum \varnothing 20 mm | 018600 20 |
| Labelling laser-etched Type | 018940 |
| DAkkS calibration "Go" / "No Go" thread plug gauge maximum \varnothing 90 mm | 019600 90 |
| Calibration Go / No Go thread plug gauge maximum \varnothing 20 mm | 028550 20 |
| DAkkS calibration "Go" / "No Go" thread plug gauge maximum \varnothing 90 mm | 028590 90 |