

## Threads No Go plug gauge, Thread: M42



### Order data

Order number	486030 M42
GTIN	4045197213143
Item class	48B

### Description

#### Version:

The ground first thread pitch removes coarse swarf in the component and prevents premature fracture of the first thread pitch. Version to DIN 2279 - 2299.

**“Go” and “No Go” gauges are separate (DIN 2240, part 2, form GE).**

#### Application:

For metric ISO threads, right-hand DIN 13.

Tolerance class 6H (up to M 1.4 = 5H).

#### Standard:

Toleranzen und Abmaße nach **DIN ISO 1502**.

#### Note:

Thread gauges for threads with other pitches, Whitworth, trapezoidal, round, UNC, UNF, NPT, and LH threads available on request.

Calibration: L11

Standard: DIN 13

Thread type: M

Thread pitch: 4.5 mm

### Technical description

Thread pitch	4.5 mm
Thread	M42
Tolerance class	6H
Thread type	M
Standard	DIN 13

Tolerance zone	H
Quality	6
Type of gauge	"No Go" gauge
Calibration	L11
Type of product	Thread NoGo plug gauge

### Services

Calibration "Go" / "No Go" thread plug gauge maximum $\varnothing$ 60 mm	018580 60
Labelling laser-etched Type	018940
DAkkS calibration "Go" / "No Go" thread plug gauge maximum $\varnothing$ 90 mm	019580 90
Calibration "Go" / "No Go" thread plug gauge maximum $\varnothing$ 60 mm	028500 60
DAkkS calibration "Go" / "No Go" thread plug gauge maximum $\varnothing$ 90 mm	028540 90