

## Fine thread "Go" / "No Go" plug gauge 6H, M × pitch: 16X1,5



### Order data

|              |               |
|--------------|---------------|
| Order number | 486100 16X1,5 |
| GTIN         | 2050001675392 |
| Item class   | 48B           |

### Description

#### Version:

The ground first thread lead chamfer (from 1 mm pitch) removes contamination in the component and prevents premature fracture of the first full thread lead chamfer.

Design to **DIN 2279 – 2299**.

**"Go" and "No Go" ends on a single handle (DIN 2240, part 1 form R).** "No Go" end marked red.

#### Application:

For metric ISO fine threads, right-hand DIN 13.

#### Standard:

Toleranzen und Abmaße nach **DIN ISO 1502**.

#### Note:

Thread gauges for threads with other pitches, Whitworth, trapezoidal, round, UNC, UNF, and NPT threads as well as left-hand threads available on request.

Calibration: L10

Standard: DIN 13

Thread type: MF

Thread pitch: 1.5 mm

### Technical description

|                 |        |
|-----------------|--------|
| Thread pitch    | 1.5 mm |
| Thread          | M16    |
| Tolerance class | 6H     |
| Standard        | DIN 13 |
| Thread type     | MF     |
| Tolerance zone  | H      |

|                 |                             |
|-----------------|-----------------------------|
| Quality         | 6                           |
| Type of gauge   | "No Go" gauge               |
| Type of gauge   | "Go" plug gauge             |
| Calibration     | L10                         |
| Type of product | Thread Go / NoGo plug gauge |

## Services

|  |           |
|--|-----------|
| Calibration Go / No Go thread plug gauge maximum Ø 20 mm           | 018600 20 |
| Labelling laser-etched Type  | 018940    |
| DAkkS calibration "Go" / "No Go" thread plug gauge maximum Ø 90 mm | 019600 90 |
| DAkkS calibration "Go" / "No Go" thread plug gauge maximum Ø 90 mm | 028590 90 |
| Calibration Go / No Go thread plug gauge maximum Ø 20 mm           | 028550 20 |