

## Fine thread "Go" / "No Go" plug gauge 6H, M × pitch: 8X1



### Order data

Order number	486100 8X1
GTIN	2050001675286
Item class	48B

### Description

#### Version:

The ground first thread lead chamfer (from 1 mm pitch) removes contamination in the component and prevents premature fracture of the first full thread lead chamfer.

Design to **DIN 2279 – 2299**.

**"Go" and "No Go" ends on a single handle (DIN 2240, part 1 form R).** "No Go" end marked red.

#### Application:

For metric ISO fine threads, right-hand DIN 13.

#### Standard:

Toleranzen und Abmaße nach **DIN ISO 1502**.

#### Note:

Thread gauges for threads with other pitches, Whitworth, trapezoidal, round, UNC, UNF, and NPT threads as well as left-hand threads available on request.

Calibration: L10

Standard: DIN 13

Thread type: MF

Thread pitch: 1 mm

### Technical description

Thread pitch	1 mm
Tolerance class	6H
Thread	M8
Standard	DIN 13
Thread type	MF
Calibration	L10

Type of product

Thread Go / NoGo plug gauge

**Services**Calibration Go / No Go thread plug gauge maximum  $\varnothing$  20 mm

018600 20

Labelling laser-etched Type

018940

DAkkS calibration "Go" / "No Go" thread plug gauge maximum  $\varnothing$  90 mm

019600 90