

## Fine thread "Go" ring gauge 6g, M × pitch: 8X0,75



### Order data

Order number	486110 8X0,75
GTIN	2050001037466
Item class	48B

### Description

**Version:**

The ground first thread lead chamfer (from 1 mm pitch) removes contamination in the component and prevents premature fracture of the first full thread lead chamfer.

Design to **DIN 2279 – 2299**.

**Application:**

For metric ISO fine threads, right-hand DIN 13.

**Standard:**

Toleranzen und Abmaße nach **DIN ISO 1502**.

**Note:**

Thread gauges for threads with other pitches, Whitworth, trapezoidal, round, UNC, UNF, and NPT threads as well as left-hand threads available on request.

Standard: DIN 13

Thread type: MF

Calibration: L12

Thread pitch: 0.75 mm

### Technical description

Thread pitch	0.75 mm
--------------	---------

Tolerance class	6g
Thread	M8
Calibration	L12
Thread type	MF
Standard	DIN 13
Type of product	Thread "Go" ring gauge

### Services

Calibration Thread ring gauge maximum $\varnothing$ 20 mm	018610 20
Labelling laser-etched Type	018940
DAkkS calibration Thread "Go" ring gauge maximum $\varnothing$ 100 mm	019610 100