

Fine thread "Go" plug gauge 6H, M × pitch: 50X1,5



Order data

| | |
|--------------|---------------|
| Order number | 486120 50X1,5 |
| GTIN | 2050001675712 |
| Item class | 48B |

Description

Version:

The ground first thread lead chamfer (from 1 mm pitch) removes contamination in the component and prevents premature fracture of the first full thread lead chamfer.

Design to **DIN 2279 – 2299**.

"Go" and "No Go" gauges are separate (DIN 2240, part 2, form GE).

Application:

For metric ISO fine threads, right-hand DIN 13.

Standard:

Toleranzen und Abmaße nach **DIN ISO 1502**.

Note:

Thread gauges for threads with other pitches, Whitworth, trapezoidal, round, UNC, UNF, and NPT threads as well as left-hand threads available on request.

Calibration: L11

Standard: DIN 13

Thread type: MF

Thread pitch: 1.5 mm

Technical description

| | |
|-----------------|--------|
| Thread pitch | 1.5 mm |
| Tolerance class | 6H |
| Thread | M50 |
| Tolerance zone | H |
| Standard | DIN 13 |

| | |
|-----------------|----------------------|
| Thread type | MF |
| Quality | 6 |
| Type of gauge | "Go" plug gauge |
| Calibration | L11 |
| Type of product | Thread Go plug gauge |

Services

| | |
|--|-----------|
| Calibration "Go" / "No Go" thread plug gauge maximum \varnothing 60 mm | 018580 60 |
| Labelling laser-etched Type | 018940 |
| DAkkS calibration "Go" / "No Go" thread plug gauge maximum \varnothing 90 mm | 019580 90 |
| DAkkS calibration "Go" / "No Go" thread plug gauge maximum \varnothing 90 mm | 028540 90 |
| Calibration "Go" / "No Go" thread plug gauge maximum \varnothing 60 mm | 028500 60 |