

## Thread plug gauge EG 6H mod., Threads: EG-M10



### Order data

Order number	486180 EG-M10
GTIN	2050001919205
Item class	48B

### Description

#### Version:

Thread gauge for testing insert threads (EG) of wire thread inserts. The ground first thread pitch removes coarse swarf in the component and prevents premature fracture of the first thread pitch. Version to DIN 2279 – 2299. **“Go” and “No Go” ends on a single handle (DIN 2240, part 1, form R).** “No Go” end marked red.

#### Application:

For metric ISO-profile insert threads (EG), right-hand DIN 8140-2.

#### Standard:

Toleranzen und Abmaße nach **DIN ISO 1502 und DIN 8140.**

Calibration: L10

Standard: DIN 8140

Thread type: EG-M

Thread pitch: 1.5 mm

### Technical description

Thread pitch	1.5 mm
Thread	EG M10
Thread type	EG-M
Standard	DIN 8140
Type of gauge	"No Go" gauge
Type of gauge	"Go" plug gauge
Calibration	L10
Type of product	Thread Go / NoGo plug gauge

## Services

Calibration Go / No Go thread plug gauge maximum Ø 200 mm	018600 200
Labelling laser-etched Type	018940
Calibration Go / No Go thread plug gauge maximum Ø 20 mm	018600 20
DAkkS calibration "Go" / "No Go" thread plug gauge maximum Ø 90 mm	019600 90
DAkkS calibration "Go" / "No Go" thread plug gauge maximum Ø 90 mm	028590 90
Calibration Go / No Go thread plug gauge maximum Ø 200 mm	028550 200
Calibration Go / No Go thread plug gauge maximum Ø 20 mm	028550 20