

Fine thread "No Go" ring gauge 6g, M × pitch: 10X0,75



Order data

Order number	486210 10X0,75
GTIN	2050001040664
Item class	48B

Description

Version:

The ground first thread lead chamfer (from 1 mm pitch) removes contamination in the component and prevents premature fracture of the first full thread lead chamfer.

Design to **DIN 2279 – 2299**.

Application:

For metric ISO fine threads, right-hand DIN 13.

Standard:

Toleranzen und Abmaße nach **DIN ISO 1502**.

Note:

Thread gauges for threads with other pitches, Whitworth, trapezoidal, round, UNC, UNF, and NPT threads as well as left-hand threads available on request.

Standard: DIN 13

Thread type: MF

Calibration: L12

Thread pitch: 0.75 mm

Technical description

Thread	M10
--------	-----

Thread pitch	0.75 mm
Tolerance class	6g
Calibration	L12
Type of gauge	"No Go" gauge
Tolerance zone	g
Standard	DIN 13
Thread type	MF
Quality	6
Type of product	Thread "No Go" ring gauge

Services

Calibration Thread ring gauge maximum \varnothing 20 mm	018610 20
Labelling laser-etched Type	018940
DAkkS calibration Thread "Go" ring gauge maximum \varnothing 100 mm	019610 100
DAkkS calibration Thread "Go" ring gauge maximum \varnothing 100 mm	028640 100
Calibration Thread ring gauge maximum \varnothing 20 mm	028600 20