



Cordless inspection camera, Manufacturer's designation: GIC120C



Order data

Order number	492710 GIC120C
GTIN	3165140817929
Item class	03B

Description

Version:

Compact cordless inspection camera for visual inspection of places that are difficult to access.

- **89 mm / 3.5 inch colour LCD display.**
- **Automatic rotation of the image ("Up is Up"™ function).**
- **Transmission of images and videos directly via microUSB cable or microSD card.**
- **Dual power source: Can be operated both with 12 V Li-ion battery, and also with standard alkaline batteries.**
- **Digital zoom for better detection of details.**
- **3-stage LED illumination for lighting dark places.**

Supplied with:

Supplied with 1 × 12 V / 2.0 Ah Li-ion battery, charger, 4 GB microSD card, camera cable No. 492716 size 1.2, micro-USB cable, hook, magnet, mirror, L-BOXX.

Packaging: Carrying case (L-Boxx)

Battery voltage: 12 V

Battery capacity: 1.5 Ah

Display size: 3.5 inch

Display resolution: 320×240 px

Camera head Ø: 8.5 mm

Length of the camera cable: 1200 mm

Technical description

Display resolution	320×240 px
Display size	3.5 inch
Battery voltage	12 V
Camera head Ø	8.5 mm
Length of the camera cable	1200 mm
Battery capacity	1.5 Ah
Weight	0.64 kg
Manufacturer's designation	GIC 120 C
Power supply	Rechargeable battery-powered
suitable battery - supplier / battery type / voltage	Bosch 12 V
Packaging	Carrying case (L-Boxx)
Type of product	Video endoscope

Accessories

Camera cable with probe Cable length 1,2 m	492718 1,2
Camera cable with probe Cable length 3,0 m	492716 3,0
Camera cable with probe Cable length 1,2 m	492716 1,2