

Cordless inspection camera, Manufacturer's designation: M12IC



Order data

Order number	492712 M12IC
GTIN	4002395001910
Item class	03L

Description

Version:

Compact cordless inspection camera for visual inspection of places that are difficult to access.

- · 69 mm / 2.7 inch rotatable colour LCD display.
- · Automatic contrast compensation and white balance.
- · Waterproof camera head with 3-step LED illumination.
- · Flexible watertight camera cable (0.9 m long).
- · Digital zoom for better detection of details.

Supplied with:

Supplied with 1× 12 V / 2.0 Ah Li-ion battery, charger, camera cable, hook, magnet, mirror,

carrying case.

Packaging: Carrying case Battery voltage: 12 V Battery capacity: 2 Ah Display size: 2.7 inch

Display resolution: 320×240 px

Camera head Ø: 9 mm

Length of the camera cable: 900 mm

Technical description

Display resolution	320×240 px
Manufacturer's designation	M12 IC
Length of the camera cable	900 mm
Display size	2.7 inch
Battery voltage	12 V
Battery capacity	2 Ah
Camera head Ø	9 mm
Weight	0.66 kg
Power supply	Rechargeable battery-powered
suitable battery - supplier / battery type / voltage	Milwaukee type B 12 V
Packaging	Carrying case
Type of product	Video endoscope