



Rigid endoscope, Ø 5.5 mm, Working length: 355 mm



Order data

Order number	492736 355
GTIN	2050001956927
Item class	49C

Description

Version:

The sturdy stainless steel tube and high-quality optics are specially well suited for rough industrial environments. Easy to connect to the required light source for the standard fibre optic cable connection (ACMI). Focusing works via a twist ring on the eyepiece. Easy focusing in the foreground and background without moving the endoscope. Bright, colour-corrected bar optics.

Suitable for :

FlexiVision 100 with HD camera head No. 492866.

Supplied with:

With interchangeable lens with direction of view 0°.

Optional extras:

LED light sources No. 492846 and No. 462860.

Note:

Using slip-on mirror sleeves the direction of view can be changed to 70° or 90°. When mirror sleeves are used the working diameter increases according to the mirror sleeve. Mirror sleeves and exchangeable lenses available on request.

Direction of view: 0 degrees

Image aperture angle: 40 degrees

Technical description

Working length	355 mm
Direction of view	0 degrees
Image aperture angle	40 degrees
Probe Ø	5.5 mm
Product name attribute	Ø 5.5 mm

Type of product	Rigid endoscope
-----------------	-----------------

Accessories

Cold light source LED Type FX4000	492860 FX4000
LED light source	492846
Endoscopy video camera CCD	492837
Flexible fibre optic cable Working length 1800 mm	492850 1800