



## Rigid micro-endoscope, Ø 1.8 mm, Working length: 95 mm



### Order data

Order number	492744 95
GTIN	2050001956965
Item class	49C

### Description

#### Version:

Small diameter for measuring small components.

The sturdy stainless steel tube and high-quality optics are specially well suited for rough industrial environments. Easy to connect to the required light source for the standard fibre optic cable connection (ACMI). Focusing works via a twist ring on the eyepiece. Easy focusing in the foreground and background without moving the endoscope. Bright, colour-corrected bar optics.

#### Suitable for :

FlexiVision 100 with HD camera head No. 492866.

#### Optional extras:

LED light sources No. 492846 and No. 462860.

#### Note:

Using slip-on mirror sleeves the direction of view can be changed to 70° or 90°. When mirror sleeves are used the working diameter increases according to the mirror sleeve. Mirror sleeves and exchangeable lenses available on request.

Direction of view: 0 degrees

Image aperture angle: 30 degrees

### Technical description

Working length	95 mm
Direction of view	0 degrees
Image aperture angle	30 degrees
Probe Ø	1.8 mm
Product name attribute	Ø 1.8 mm
Type of product	Rigid endoscope

---

## Accessories

Endoscopy video camera CCD	492837
Cold light source LED Type FX4000	492860 FX4000
Flexible fibre optic cable Working length 1800 mm	492850 1800
LED light source	492846