

HOLEX

Video endoscope without probe



Order data

Order number	492921
GTIN	4045197739049
Item class	42L

Description

Version:

HOLEX video endoscope with large LCD display showing true-scale details, and comprehensive functions. The sun shade offers additional protection when in sunlight. The unit can be held steady using the two handles. The base unit is compatible with all HOLEX endoscope probes No. 492932 – 492944.

- **Base unit with 7 inch LCD display (image cut-out 6 inches).**
- **Zoom mode; 3 stages of digital zoom: 1.5×, 2× and 5×.**
- **Images and video recordings can be saved.**
- **USB and AV output. The integral USB and AV outputs allows your images and videos to be transferred to a PC.**
- **Integral rechargeable Li-ion battery with 5 hour capacity.**
- **IP55 protection.**
- **90° image rotation clockwise using the control button.**

Advantage:

- **Exceptionally sturdy, very suitable for outdoor use.**
- **Very large image aperture of 6 inches.**
- **Display resolution 640 × 480 px.**
- **Image aperture can be divided for parallel display of 0° and 90° views.**
- **Facility for adding comments by sound recording. The built-in microphone can be used for recording comments during the inspection. This eliminates the requirement for tedious writing and compiling of notes.**
- **Selected settings can be clearly shown directly on the display.**

Function:

IP55: Protected against jets of water from all directions and protected against penetration of dust into the inside (protected against dust), also completely protected against touching.

Supplied with:

Sturdy watertight and dust-tight transport case, SD memory card (16 GB), power adapter (AC 100 – 240 V / 50 – 60 Hz), USB data cable, AV cable, cleaning kit. **Without probe.**

Optional extras:

Endoscope probes No. 492932 – 492944.

Recording format: JPEG / AVI (30fps)

Display resolution: 640×480 px

depth of focus when focussed: 16 – 60 mm

Operating temperature: 0 - 60 °C

Weight: 1.3 kg

Technical description

Weight	1.3 kg
Operating temperature	0 - 60 °C
Length	240 mm
Display resolution	640×480 px
Width	154 mm
Height	47 mm
Recording format	JPEG / AVI (30fps)
depth of focus when focussed	16 – 60 mm
Power supply	Rechargeable battery-powered
Type of product	Video endoscope

Accessories

Endoscope probe, flexible Probe length 2000 mm	492940 2000
Endoscope probe, semi-rigid Probe length 1000 mm	492936 1000
Endoscope probe, flexible Probe length 2000 mm	492938 2000
Adapter for 0° and 90° directions of view	492898
	492944 1500

Endoscope probe, elbow bend, flexible Probe length 1500 mm

Endoscope probe, flexible Probe length 1000 mm	492937 1000
--	-------------

Endoscope probe, elbow bend, flexible Probe length 3000 mm	492944 3000
--	-------------

Endoscope probe, semi-rigid, switchable Probe length 1000 mm	492932 1000
--	-------------

Endoscope probe, semi-rigid Probe length 2000 mm	492934 2000
--	-------------

Endoscope probe, semi-rigid Probe length 1000 mm	492934 1000
--	-------------

Endoscope probe, elbow bend, flexible Probe length 1000 mm	492942 1000
--	-------------