

HOLEX
Endoscope probe, flexible, 5.5 mm Ø, Probe length: 2000 mm

Order data

Order number	492940 2000
GTIN	4045197565426
Item class	42L

Description
Version:

Sturdy watertight probe head (IP67) of stainless steel with dimmable white LEDs. Direction of view 0°.

Very high image quality with 16.7 million colours.

Illumination mode: Control switch for turning the image illumination on and off. For use in large voids and/or very dark surroundings.

Side-LED mode: When the screw-on probe mirror is used, activation of the side LEDs avoids generation of confusing reflections.

Image rotation: 90° image rotation clockwise using the control button.

Image aperture angle 60.7°.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Application:

Ideal for inspection of voids where access is difficult, e.g. **automotive:** Engine, gearbox, fuel tank, bodywork, dashboard, appraisal. **Aerospace:** engines, turbines, pipework, and wiring systems. **Buildings:** Assessment of the structure of buildings, water damage, pest infestation. **Pipework systems:** weld seams, traces of foreign bodies, leaks. **Hydraulic systems:** cylinders, leaks. **Heating - sanitation - air conditioning:** ovens, furnaces, boilers, air conditioning systems,

drainage systems. **Pest control:** Bees' nests, wasps' nests, birds' nests, insect entry points. **Police, customs:** Vehicle checking, goods checking.

Suitable for :

All endoscope versions No. 492921; 492924; 492925; 492928.

Supplied with:

Screw-on probe mirror 110°.

Optional extras:

Adapter No. 492896 for using the probes with photo / video endoscope No. 492890 size 2000.

Note:

Other types of probe (up to 30 m) with other probe head Ø and directions of view available on request.

Probe for pipework inspection:

- **Head Ø: 28 mm**
- **Probe length: 22 m**
- **Image aperture angle: 150°**
- **8 high-intensity LEDs.**

Camera resolution: 640×480 px

IP Index of Protection: IP 67

Technical description

Probe length	2000 mm
IP Index of Protection	IP 67
Camera resolution	640×480 px
Probe Ø	5.5 mm
Product name attribute	5.5 mm Ø
Type of product	Probe for endoscope

Accessories

Probe ball for Ø 5.5 mm	492952
Probe mirror for Ø 5.5 mm Angle of view 110 Degrees	492950 110
Probe mirror for Ø 5.5 mm Angle of view 90 Degrees	492950 90
Probe mirror for Ø 5.5 mm Angle of view 70 Degrees	492950 70