

**HOLEX****Endoscope probe, elbow bend, flexible, 6 mm Ø, Probe length: 1000 mm****Order data**

Order number	492942 1000
GTIN	4045197565433
Item class	42L

**Description****Version:**

Sturdy watertight probe head (IP67) of stainless steel with dimmable white LEDs. Direction of view 0°.

Very high image quality with 16.7 million colours.

**Illumination mode:** Control switch for turning the image illumination on and off. For use in large voids and/or very dark surroundings.

**Side-LED mode:** When the screw-on probe mirror is used, activation of the side LEDs avoids generation of confusing reflections.

**Image rotation:** 90° image rotation clockwise using the control button.

**Elbow bend probe head:** Probe with hand grip and setting handle for bending the camera head in two directions (maximum 2× 155°). In conjunction with the probe mirror supplied, this allows inspection even of a recess that faces in the opposite direction to the insertion of the probe.

A stop function for the desired angular position allows non-fatiguing working. Probe tip with braided metal protective sheath.

Image aperture angle 87.1°.

**Function:**

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

**Application:**

Ideal for inspection of voids where access is difficult, e.g. **automotive:** Engine, gearbox, fuel tank, bodywork, dashboard, appraisal. **Aerospace:** engines, turbines, pipework, and wiring systems. **Buildings:** Assessment of the structure of buildings, water damage, pest infestation. **Pipework systems:** weld seams, traces of foreign bodies, leaks. **Hydraulic systems:** cylinders, leaks. **Heating - sanitation - air conditioning:** ovens, furnaces, boilers, air conditioning systems, drainage systems. **Pest control:** Bees' nests, wasps' nests, birds' nests, insect entry points. **Police, customs:** Vehicle checking, goods checking.

**Suitable for :**

All endoscope versions No. 492921; 492924; 492925; 492928.

**Supplied with:**

Screw-on probe mirror 70°.

**Optional extras:**

Adapter No. 492896 for using the probes with photo / video endoscope No. 492890 size 2000.

**Note:**

Other types of probe (up to 30 m) with other probe head Ø and directions of view available on request.

**Probe for pipework inspection:**

- **Head Ø: 28 mm**
- **Probe length: 22 m**
- **Image aperture angle: 150°**
- **8 high-intensity LEDs.**

Camera resolution: 640×480 px

IP Index of Protection: IP 67

## Technical description

Probe length	1000 mm
IP Index of Protection	IP 67
Camera resolution	640×480 px
Probe Ø	6 mm
Product name attribute	6 mm Ø
Type of product	Probe for endoscope