# Mitutoyo

Scale unit vertical, Measuring range: 200 mm



## Order data

Order number	499402 200
GTIN	4946368128405
Item class	44A

## Description

#### Version:

Scale unit with capacitive electronic measuring system. For vertical installation.

With **absolute electronics** and large easy-to-read display digits. One-off setting of the zero position, which remains the absolute zero point until the battery has to be replaced (approx. 1.5 years). Maximum measuring precision with very high speed of travel. ZERO/ABS function – zero setting and changeover between relative and absolute measurement.

#### Application:

Suitable for measuring and positioning tasks on machine tools, jigs, etc.

#### Supplied with:

1 battery No. 081560 size 357. **Optional extras:** Data cable No. 497085. Measured value saving: once-off setting of the zero position Calibration: Price on request Scale divisions: 0.01 mm Error limit: 0.03 mm Overall length  $L_2$ : 320 mm Length of the measuring beam  $L_1$ : 344 mm Weight: 310 g

# **Technical description**

Measuring range	0 - 200 mm
Weight	310 g
Scale divisions	0.01 mm
Calibration	Price on request
Overall length L <sub>2</sub>	320 mm
Length of the measuring beam L <sub>1</sub>	344 mm
Error limit	0.03 mm
Article no of the battery / rechargeable battery fitted	081560 357
Number of batteries contained	1
Power supply	Battery-powered
Standard	Manufacturer's standard
Interface	Digimatic interface
Measured value saving	once-off setting of the zero position
Measurement technology	digital
Type of product	Scale unit

## Services

Labelling laser-etched Type	018940

## Accessories

Connecting cable with data switch Type USB2	497085 USB2
Connecting cable with data switch Type D2	497085 D2
Transmitter Type S11E	498966 S11E
Multi-receiver / USB keyboard interface Type	498975
Button cell / special battery Battery type 357	081560 357
Receiver / USB keyboard interface Type	498965
Connecting cable with data switch Type D1	497085 D1