



Burr, coated Z 4 – fine, diamond cut, Carbide TiAlN, Type: F1225



Order data

Order number	540560 F1225
GTIN	4027497279135
Item class	56L

Description

Version:

Shank Ø 6 mm.

LUKAS burrs are manufactured from high performance carbide grades with high wear resistance and maximum cutting edge stability, using only the latest CNC machines. Steel shanks are used when the head diameter is larger than the shank diameter, otherwise they are made from solid carbide.

Additional TiAlN coating for longer working life and temperature resistance.

For high thermal and mechanical loadings (Heavy Duty). **Round arch shape** (RBF).

Application:

Suitable for use with power tools and industrial robots, on almost all materials. For deburring, edge breaking, cleaning, weld and surface preparation.

Shank Ø: 6 mm

Shape description: round arch

Head Ø: 12 mm

Head length L₁: 25 mm

Overall length: 65 mm

Shank Ø: 6 mm

Technical description

Tooth type abbreviation	Z4
Toothing grit designation	fine
Overall length	65 mm
Shape	F1225
Shape description	round arch

Head length L ₁	25 mm
Head Ø	12 mm
Type of cut	staggered teeth
Shank Ø	6 mm
Tool material	Carbide TiAlN
Coating	TiAlN
Type of product	Burr