Garant

Grinding point fine, AR, Type: ZY2025



Order data

| Order number | 550700 ZY2025 |
|--------------|---------------|
| GTIN | 4045197239365 |
| Item class | 51E |

Description

Version:

GARANT grinding points (OSA certified and tested to DIN EN 12 413) are specially designed for hardness, bonding, grit type and grit size for the specific applications and cover a very wide application range. Minimal radial run-out ensures vibration-free grinding which is good for man, machine, and component. GARANT grinding points are generally suitable for **edge and surface grinding** and provide you with maximum material removal rates, long service life, and consistent surface finish quality of the component.

Ceramic bonded grinding points in **pink electro-carborundum (AR).** Medium-hard version. Fine grit. Shank length 40 mm.

Application:

For general-purpose grinding of **unalloyed and low-alloy** steels and **cast iron.** Recommended cutting speed 30 – 50 m/s. Grinding medium code: A Head Ø: 20 mm Head length: 25 mm Shank Ø: 6 mm

Technical description

| Shaft length | 40 mm |
|------------------|-------|
| Head Ø | 20 mm |
| Grit designation | fine |
| Shank Ø | 6 mm |
| Head length | 25 mm |

© Hoffmann GmbH Qualitätswerkzeuge

| Grinding media | Standard aluminium oxide (A) |
|------------------------|------------------------------|
| Grinding medium code | А |
| Product name attribute | AR |
| Type of product | Grinding point |