

Grinding disc (CER), Ø 50.8 mm, Grit: 80



Order data

| Order number | 553921 80 |
|--------------|---------------|
| GTIN | 4045197526182 |
| Item class | 51E |

Description

Version:

Optimum connection between the backing pad and grinding disc by the quick-clamping system (internal thread). Easy and quick disc replacement by hand, even after heavy use.

Sanding disc is centralised, resulting in vibration-free concentricity.

Ceramic grit (CER) ideal for working on stainless steels and nickel alloys. High removal rate and cool cut.

Application:

For efficient sanding down of small areas, even with varying contours in tool, mould and model making, machine, plant and container building. Reduced tool changing times save costs on multi-stage operations.

Note:

Other dimensions and grits available on request.

Grinding medium code: Ceramic maximum speed: 25000 rpm

Technical description

| Grit | 80 |
|------------------------|--------------------|
| Disc Ø | 50.8 mm |
| Grinding media | Ceramic grit (CER) |
| Grinding medium code | Ceramic |
| Product name attribute | Ø 50.8 mm |

| maximum speed | 25000 rpm |
|-----------------|----------------|
| Type of product | Grinding wheel |

Accessories

Rubber backing pad shank \varnothing 6 mm medium hard External \varnothing 50M mm

553920 50M