


3M Roloc™
Grinding disc 984F, Ø 76.2 mm, Grit: 36



Order data

Order number	554006 36
GTIN	30051141277029
Item class	53M

Description

Version:

Very high material removal rate and service life due to the use of self-sharpening ceramic grit (CER).

The Roloc™, Combidisc® CDR **quick-change system** with a plastic thread permits safe abrasive tool changing "with a single twist of the wrist" in a very short time.

With precision formed **Cubitron™ II** grit.

Application:

For efficient abrasion of small areas, even with changing contours. Reduced tool changing times save costs on multi-stage operations.

Use in conjunction with hard support pad No. 554089.

Note:

Roloc™ bristle discs can be found from No. 573510 onwards.

Grinding medium code: Ceramic

maximum speed: 20000 rpm

Technical description

Grit	36
Disc Ø	76.2 mm

Grinding media	Cubitron™ II
Grinding medium code	Ceramic
Grinding media backing	stable-edged underlay
Product name attribute	Ø 76.2 mm
Manufacturer's designation	984F
maximum speed	20000 rpm
Type of product	Grinding wheel

Accessories

Rubber backing pad shank Ø 6 mm hard External Ø 75 mm	554089 75
Rubber backing pad with mounting M14 hard External Ø 75 mm	554088 75
Rubber backing pad with M14 mounting hard External Ø 75 mm	554094 75