
#### **3M** Roloc™

Grinding disc 237AA, Ø 76.2 mm, Grit: 120



## Order data

Order number	554009 120
GTIN	2050001743084
Item class	53M

### Description

#### Version:

The Roloc<sup>™</sup>, Combidisc<sup>®</sup> CDR **quick-change system** with a plastic thread permits safe abrasive tool changing "with a single twist of the wrist" in a very short time.

237AA Trizact<sup>™</sup> with fine-structured pyramidal surface of micro-Aluminium Oxide mineral particles.

#### **Application:**

For efficient abrasion of small areas, even with changing contours. Reduced tool changing times save costs on multi-stage operations.

Specially for **surface finishing** of hard and difficult-to-grind materials such as **stainless steel**, **titanium**, **high-alloy steels** etc. Consistently **reproducible finish and long service life** compared to grinding discs of a similar grit grade.

Note:

Roloc<sup>™</sup> bristle discs can be found from No. 573510 onwards. Grinding medium code: A maximum speed: 20000 rpm 3M grit designation: A160

Colour code: white

## **Technical description**

# roup 🖈 Hoffmann Group

3M grit designation	A160
Colour code	white
Grit	120
Disc Ø	50.8 mm
Grinding media	Aluminium oxide mineral particles (A)
Grinding medium code	А
Product name attribute	Ø 76.2 mm
Manufacturer's designation	237AA Trizact™
maximum speed	20000 rpm
Type of product	Grinding wheel

## Accessories

Rubber backing pad shank Ø 6 mm soft External Ø 75 mm	554091 75
Rubber backing pad shank Ø 6 mm medium External Ø 75 mm	554092 75
Rubber backing pad with M14 mounting hard External $\varnothing$ 75 mm	554094 75
Rubber backing pad shank Ø 6 mm hard External Ø 75 mm	554089 75
Plastic backing pad shank Ø 6 mm External Ø 75 mm	554090 75
Rubber backing pad with mounting M14 hard External $arnothing$ 75 mm	554088 75
Rubber backing pad shank Ø 6 mm medium hard External Ø 75 mm	554093 75