

Garant

Grinding disc (CER), Ø 76.2 mm, Grit: 120



Order data

Order number	554013 120
GTIN	4045197802354
Item class	51E

Description

Version:

The Roloc™, Combidisc® CDR **quick-change system** with a plastic thread permits safe abrasive tool changing “with a single twist of the wrist” in a very short time.

Very high material removal rate and service life due to the use of self-sharpening ceramic grit (CER).

Application:

Use in conjunction with hard support pad No. 554089.

For efficient abrasion of small areas, even with changing contours. Reduced tool changing times save costs on multi-stage operations.

Note:

Roloc™ bristle discs can be found from No. 573510 onwards.

Grinding medium code: Ceramic

maximum speed: 20000 rpm

Technical description

Grinding media	Ceramic grit
Grinding medium code	Ceramic

Grinding media backing	Fibre underlay
Product name attribute	Ø 76.2 mm
maximum speed	20000 rpm
Type of product	Grinding wheel

Accessories

Rubber backing pad shank Ø 6 mm soft External Ø 75 mm	554091 75
Rubber backing pad with M14 mounting hard External Ø 75 mm	554094 75
Rubber backing pad with mounting M14 hard External Ø 75 mm	554088 75
Rubber backing pad shank Ø 6 mm medium hard External Ø 75 mm	554093 75
Plastic backing pad shank Ø 6 mm External Ø 75 mm	554090 75
Rubber backing pad shank Ø 6 mm hard External Ø 75 mm	554089 75
Rubber backing pad shank Ø 6 mm medium External Ø 75 mm	554092 75