Garant

Grinding disc (CER), Ø 76.2 mm, Grit: 36



Order data

| Order number | 554013 36 |
|--------------|---------------|
| GTIN | 4045197526021 |
| Item class | 51E |

Description

Version:

The Roloc™, Combidisc® CDR **quick-change system** with a plastic thread permits safe abrasive tool changing "with a single twist of the wrist" in a very short time.

Very high material removal rate and service life due to the use of self-sharpening ceramic grit (CER).

Application:

Use in conjunction with hard support pad No. 554089.

For efficient abrasion of small areas, even with changing contours. Reduced tool changing times save costs on multi-stage operations.

Note:

Roloc™ bristle discs can be found from No. 573510 onwards.

Grinding medium code: Ceramic maximum speed: 20000 rpm

Technical description

| Grit | 36 |
|--------|---------|
| Disc Ø | 76.2 mm |



| Grinding media | Ceramic grit |
|------------------------|----------------|
| Grinding medium code | Ceramic |
| Grinding media backing | Fibre underlay |
| Product name attribute | Ø 76.2 mm |
| maximum speed | 20000 rpm |
| Type of product | Grinding wheel |

Accessories

| Rubber backing pad shank Ø 6 mm soft External Ø 75 mm | 554091 75 |
|--|-----------|
| Rubber backing pad with mounting M14 hard External Ø 75 mm | 554088 75 |
| Rubber backing pad shank Ø 6 mm hard External Ø 75 mm | 554089 75 |
| Plastic backing pad shank Ø 6 mm External Ø 75 mm | 554090 75 |
| Rubber backing pad shank \varnothing 6 mm medium hard External \varnothing 75 mm | 554093 75 |
| Rubber backing pad shank Ø 6 mm medium External Ø 75 mm | 554092 75 |
| Rubber backing pad with M14 mounting hard External Ø 75 mm | 554094 75 |