爨 PFERD

Combidisc® grinding disc (SiC), Ø 50.8 mm, Grit: 120



Order data

Order number	554023 120
GTIN	4007220778500
Item class	55G

Description

Version:

The Roloc™, Combidisc® CDR **quick-change system** with a plastic thread permits safe abrasive tool changing "with a single twist of the wrist" in a very short time.

Sharp-edged Silicon Carbide grit (SiC) for aggressive grinding with light pressure. **Application:**

For efficient abrasion of small areas, even with changing contours. Reduced tool changing times save costs on multi-stage operations.

Specially suitable for grinding titanium alloys, aluminium, copper and bronze.

Note:

Roloc™ bristle discs can be found from No. 573510 onwards.

Grinding medium code: SiC maximum speed: 25000 rpm

Technical description

Grit	120
Disc Ø	50.8 mm
Grinding media	Silicon carbide (SiC)
Grinding medium code	SiC



Product name attribute	Ø 50.8 mm
maximum speed	25000 rpm
Type of product	Grinding wheel

Accessories

Rubber backing pad shank \varnothing 6 mm medium hard External \varnothing 50 mm	554093 50
Rubber backing pad shank Ø 6 mm hard External Ø 50 mm	554089 50
Trabber backing pad sharik a diffinitial diexectial a so tilli	33 1003 30
Rubber backing pad shank Ø 6 mm soft External Ø 50 mm	554091 50
Rubber backing pad shank Ø 6 mm medium External Ø 50 mm	554092 50
Plastic backing pad shank Ø 6 mm External Ø 50 mm	554090 50