### **際 PFERD**

Combidisc<sup>®</sup> grinding disc (SiC), Ø 50.8 mm, Grit: 60



## Order data

Order number	554023 60
GTIN	4007220778487
Item class	55G

### Description

#### Version:

The Roloc<sup>™</sup>, Combidisc<sup>®</sup> CDR **quick-change system** with a plastic thread permits safe abrasive tool changing "with a single twist of the wrist" in a very short time.

Sharp-edged Silicon Carbide grit (SiC) for aggressive grinding with light pressure.

#### Application:

For efficient abrasion of small areas, even with changing contours. Reduced tool changing times save costs on multi-stage operations.

Specially suitable for grinding titanium alloys, aluminium, copper and bronze.

#### Note:

**Roloc™ bristle discs** can be found from No. 573510 onwards.

Grinding medium code: SiC

maximum speed: 25000 rpm

## **Technical description**

Grit	60
Disc Ø	50.8 mm
Grinding media	Silicon carbide (SiC)
Grinding medium code	SiC

Product name attribute	Ø 50.8 mm
maximum speed	25000 rpm
Type of product	Grinding wheel

# Accessories

Rubber backing pad shank Ø 6 mm hard External Ø 50 mm	554089 50
Rubber backing pad shank Ø 6 mm soft External Ø 50 mm	554091 50
Rubber backing pad shank Ø 6 mm medium External Ø 50 mm	554092 50
Rubber backing pad shank Ø 6 mm medium hard External Ø 50 mm	554093 50
Plastic backing pad shank Ø 6 mm External Ø 50 mm	554090 50