3M Roloc™

Abrasive disc 777F, 50.8 mm Ø, Grit: 36



Order data

Order number	554025 36
GTIN	2050001747914
Item class	53M

Description

Version:

The Roloc™, Combidisc® CDR **quick-change system** with a plastic thread permits safe abrasive tool changing "with a single twist of the wrist" in a very short time.

Very high material removal rate and service life due to the use of self-sharpening ceramic grit (CER).

Application:

For efficient abrasion of small areas, even with changing contours. Reduced tool changing times save costs on multi-stage operations.

Note:

Roloc™ bristle discs can be found from No. 573510 onwards.

Grinding medium code: Ceramic maximum speed: 25000 rpm

Colour code: brown

Technical description

Grit	36
Colour code	brown
Disc Ø	50.8 mm
Grinding media	Ceramic grit (CER)



Grinding medium code	Ceramic
Product name attribute	50.8 mm Ø
Manufacturer's designation	777F
suitable for quick-change system	Roloc™
maximum speed	25000 rpm
Type of product	Grinding wheel

Accessories

Rubber backing pad shank Ø 6 mm soft External Ø 50 mm	554091 50
Rubber backing pad shank Ø 6 mm medium hard External Ø 50 mm	554093 50
Rubber backing pad shank Ø 6 mm hard External Ø 50 mm	554089 50
Plastic backing pad shank Ø 6 mm External Ø 50 mm	554090 50
Rubber backing pad shank Ø 6 mm medium External Ø 50 mm	554092 50