爨 PFERD

Combidisc® grinding disc Diamond, Ø 50.8 mm, Grit: 220



Order data

Order number	554033 220
GTIN	4007220750506
Item class	55G

Description

Version:

The Roloc[™], Combidisc[®] CDR **quick-change system** with a plastic thread permits safe abrasive tool changing "with a single twist of the wrist" in a very short time.

Grinding discs with diamond grit (D) for **extremely hard materials** such as carbide, glass, ceramic, CRP/GRP and wear protection coatings (such as enamel). Use on hard or medium-hard backing pads.

Application:

For efficient abrasion of small areas, even with changing contours. Reduced tool changing times save costs on multi-stage operations.

Note:

Roloc™ bristle discs can be found from No. 573510 onwards.

Grinding medium code: D maximum speed: 7500 rpm equivalent to grit size: 76 µm

Technical description

Grit	220
Disc Ø	50.8 mm
equivalent to grit size	76 μm

Grinding media	Diamond
Grinding medium code	D
Product name attribute	Ø 50.8 mm
maximum speed	7500 rpm
Type of product	Grinding wheel

Accessories

Rubber backing pad shank Ø 6 mm hard External Ø 50 mm	554089 50
Dubbankadian and sharel QC area and the Francis QC	
Rubber backing pad shank Ø 6 mm medium External Ø 50 mm	554092 50
Bubbar backing and shapk Q 6 mm madium hard External	
Rubber backing pad shank \emptyset 6 mm medium hard External \emptyset 50 mm	554093 50
Plastic backing pad shank Ø 6 mm External Ø 50 mm	554090 50
D.I. I. I. I. I. C.	FF 4004 F0
Rubber backing pad shank Ø 6 mm soft External Ø 50 mm	554091 50