### 爨 PFERD

## Combidisc® grinding disc Diamond, Ø 50.8 mm, Grit: 60



## **Order data**

Order number	554033 60
GTIN	4007220750483
Item class	55G

## **Description**

#### **Version:**

The Roloc<sup>™</sup>, Combidisc<sup>®</sup> CDR **quick-change system** with a plastic thread permits safe abrasive tool changing "with a single twist of the wrist" in a very short time.

Grinding discs with diamond grit (D) for **extremely hard materials** such as carbide, glass, ceramic, CRP/GRP and wear protection coatings (such as enamel). Use on hard or medium-hard backing pads.

### **Application:**

For efficient abrasion of small areas, even with changing contours. Reduced tool changing times save costs on multi-stage operations.

### Note:

**Roloc™ bristle discs** can be found from No. 573510 onwards.

Grinding medium code: D maximum speed: 7500 rpm equivalent to grit size: 251 µm

## **Technical description**

Grit	60
Disc Ø	50.8 mm
equivalent to grit size	251 μm

Grinding media	Diamond
Grinding medium code	D
Product name attribute	Ø 50.8 mm
maximum speed	7500 rpm
Type of product	Grinding wheel

# **Accessories**

Rubber backing pad shank $\varnothing$ 6 mm hard External $\varnothing$ 50 mm	554089 50
Plastic backing pad shank Ø 6 mm External Ø 50 mm	554090 50
Rubber backing pad shank Ø 6 mm soft External Ø 50 mm	554091 50
Rubber backing pad shank Ø 6 mm medium hard External	554093 50
Ø 50 mm	
Rubber backing pad shank Ø 6 mm medium External Ø 50 mm	554092 50
ППП	