

Abrasive flap disc (ZA), Ø 50.8 mm, Grit: 60



Order data

Order number	554035 60
GTIN	4027497339518
Item class	56L

Description

Version:

Flat, compact arrangement of the strips for **weld seam dressing** and for **deburring work**.

The Roloc™, Combidisc® CDR **quick-change system** with a plastic external thread permits safe abrasive tool changing "with a single twist of the wrist" in a very short time.

Compared to conventional grinding discs, **mini-flap discs** with abrasive strips arranged at a very steep angle offer a **longer working life**, **more flexible grinding characteristics** and a **more even surface finish** (roughness value) down to the wear limit.

Application:

For efficient abrasion of small areas, even with changing contours. Reduced tool changing times save costs on multi-stage operations.

Note:

Roloc™ bristle discs can be found from No. 573510 onwards.

Thread: Roloc™ quick-change system

maximum speed: 20000 rpm

Technical description

Grit	60
Disc Ø	50.8 mm
Grinding media	Zirconium abrasive (ZA)
Grinding medium code	ZA



Grinding media backing	Plastic pad
Product name attribute	Ø 50.8 mm
Thread	Roloc™ quick-change system
maximum speed	20000 rpm
Type of product	Abrasive flap disc

Accessories

Rubber backing pad shank Ø 6 mm soft External Ø 50 mm	554091 50
Rubber backing pad shank \varnothing 6 mm medium hard External \varnothing 50 mm	554093 50
Rubber backing pad shank Ø 6 mm medium External Ø 50 mm	554092 50
Rubber backing pad shank Ø 6 mm hard External Ø 50 mm	554089 50
Plastic backing pad shank Ø 6 mm External Ø 50 mm	554090 50