

3M Roloc™
Fleece disc GB-DR, Ø 76.2 mm, Grit equivalent: 50


Order data

Order number	554063 50
GTIN	2050001747839
Item class	53M

Description

Version:

The Roloc™, Combidisc® CDR **quick-change system** with a plastic thread permits safe abrasive tool changing “with a single twist of the wrist” in a very short time.

Fleece disc **with aggressive Cubitron grit (CER)** in combination with wear-resistant fabric.

Application:

For efficient abrasion of small areas, even with changing contours. Reduced tool changing times save costs on multi-stage operations.

Allows **material removal** and **burr-free finishing** with only a single tool. High edge stability and long working life.

Note:

Roloc™ bristle discs can be found from No. 573510 onwards.

Iron, sulphur and chlorine constituents: < 0.1 %

maximum speed: 18000 rpm

Grit designation: extra coarse

Version: coarse super duty

Technical description

Version	coarse super duty
Grit equivalent	50
Grit designation	extra coarse

Disc Ø	76.2 mm
Grinding media	Cubitron™ grinding grit
Grinding medium code	Ceramic
Iron, sulphur and chlorine constituents	< 0.1 %
Product name attribute	Ø 76.2 mm
Manufacturer's designation	GB-DR
maximum speed	18000 rpm
Type of product	Non-woven abrasive

Accessories

Rubber backing pad shank Ø 6 mm medium hard External Ø 75 mm	554093 75
Rubber backing pad with M14 mounting hard External Ø 75 mm	554094 75
Rubber backing pad shank Ø 6 mm soft External Ø 75 mm	554091 75
Rubber backing pad shank Ø 6 mm medium External Ø 75 mm	554092 75
Plastic backing pad shank Ø 6 mm External Ø 75 mm	554090 75
Rubber backing pad shank Ø 6 mm hard External Ø 75 mm	554089 75
Rubber backing pad with mounting M14 hard External Ø 75 mm	554088 75