3M Roloc™

Cleaning disc (A), Ø 50.8 mm, Fleece version: MED



Order data

Order number	554064 MED
GTIN	50048011641909
Item class	53M

Description

Version:

The Roloc[™], Combidisc[®] CDR **quick-change system** with a plastic thread permits safe abrasive tool changing "with a single twist of the wrist" in a very short time.

Coarse cleaning disc with synthetic nylon fleece evenly impregnated with abrasive grit on glass fibre pad. Open structure, will not clog. Combines **cleaning** with imparting a **fine finish**.

Application:

For efficient abrasion of small areas, even with changing contours. Reduced tool changing times save costs on multi-stage operations.

For rust removal, paint removal, dressing weld seams and removing surface dirt.

Note:

Roloc™ bristle discs can be found from No. 573510 onwards.

Iron, sulphur and chlorine constituents: < 0.1 %

Grit designation: coarse Degree of hardness: medium 3M designation: BF-DR maximum speed: 18000 rpm

Technical description

maximum speed	18000 rpm
maximum speed	18000 rpm



Grit designation	coarse
Degree of hardness	medium
3M designation	BF-DR
Disc Ø	50.8 mm
Grinding media	Standard aluminium oxide (A)
Grinding medium code	Α
Iron, sulphur and chlorine constituents	< 0.1 %
Product name attribute	Ø 50.8 mm
Type of product	Rough cleaning non- woven abrasive mesh

Accessories

Rubber backing pad shank Ø 6 mm hard External Ø 50 mm	554089 50
Plastic backing pad shank Ø 6 mm External Ø 50 mm	554090 50
Rubber backing pad shank Ø 6 mm medium hard External Ø 50 mm	554093 50
Rubber backing pad shank Ø 6 mm soft External Ø 50 mm	554091 50
Rubber backing pad shank Ø 6 mm medium External Ø 50 mm	554092 50