

3M Roloc™
Compact disc XL-DR, Ø 76.2 mm, Grit equivalent: 280


Order data

Order number	554067 280
GTIN	30048011171846
Item class	53M

Description

Version:

The Roloc™, Combidisc® CDR **quick-change system** with a plastic thread permits safe abrasive tool changing “with a single twist of the wrist” in a very short time.

Fibre fleece with resin-bonded grit, **compacted disc shape**.

Application:

For efficient abrasion of small areas, even with changing contours. Reduced tool changing times save costs on multi-stage operations.

Especially suitable for **finish grinding and deburring**. Leaves a **fine finish** and reduces the roughness of all materials.

Note:

Roloc™ bristle discs can be found from No. 573510 onwards.

Iron, sulphur and chlorine constituents: < 0.1 %

maximum speed: 15000 rpm

Grinding medium code: SiC

Grit designation: fine

Degree of hardness: soft

Version: 2 S fine

Technical description

Grit equivalent	280
-----------------	-----

Version	2 S fine
Degree of hardness	soft
Grit designation	fine
Disc Ø	76.2 mm
Grinding medium code	SiC
Grinding media	Silicon carbide (SiC)
Iron, sulphur and chlorine constituents	< 0.1 %
Product name attribute	Ø 76.2 mm
Manufacturer's designation	XL-DR
maximum speed	15000 rpm
Type of product	Compact disc

Accessories

Rubber backing pad with M14 mounting hard External Ø 75 mm	554094 75
Rubber backing pad shank Ø 6 mm hard External Ø 75 mm	554089 75
Plastic backing pad shank Ø 6 mm External Ø 75 mm	554090 75
Rubber backing pad shank Ø 6 mm soft External Ø 75 mm	554091 75
Rubber backing pad shank Ø 6 mm medium External Ø 75 mm	554092 75
Rubber backing pad with mounting M14 hard External Ø 75 mm	554088 75
Rubber backing pad shank Ø 6 mm medium hard External Ø 75 mm	554093 75