



Aluminium Oxide (A) finishing belt KK841F, 75×3500 mm, Grit: 320



Order data

Order number	558171 320
GTIN	4018875019290
Item class	56V

Description

Version:

Highly flexible finishing belt with **Aluminium Oxide (A)**. Moulds ideally to the workpiece contours. The active grinding layer (**TOP size**) ensures cool grinding and which serves as a separation layer for materials which tend to smearing.

Application:

Ideally suited to **contour grinding** or **profile grinding** with concave or convex contact rollers. Particularly suitable for **chromium-nickel steel, high-alloy steel, nickel based alloys, brass and bronze** and also titanium and aluminium. Machining of fittings, fittings, turbine blades, very delicate parts, implants and surgical instruments. For use in **manual or robot grinding** on popular narrow finishing machines from IMM, Löser, Greif, Rema etc.

Note:

Other grit sizes, qualities, and dimensions are available on request in line with the manufacturer's minimum order quantities. Unless specified otherwise on the order, belts will be supplied with standard joints. See No. 568526ff for spare finishing belts for burnishing machines.

Iron, sulphur and chlorine constituents: < 0.1 %

Technical description

Grit	320
------	-----

Grinding media	Standard aluminium oxide (A)
Grinding medium code	A
Iron, sulphur and chlorine constituents	< 0.1 %
Linishing belt width	75 mm
Linishing belt length	3500 mm
Product name attribute	75×3500 mm
Manufacturer's designation	KK841F
Type of product	Linishing belt