# **3M** Linishing belt Cubitron™II 984F, 50×3500 mm, Grit: 80



# Order data

| Order number | 558448 80     |
|--------------|---------------|
| GTIN         | 4046719937264 |
| Item class   | 535           |

# Description

#### Version:

**Cubitron™ II linishing belt 984F** with pure precision-shaped ceramic grit on stable YF polyester backing. **High-performance linishing belt for preliminary linishing** on stationary linishing machines. Cool cutting thanks to grinding aids.

### YF-fabric (robust) for stationary linishing machines with high contact forces.

#### **Application:**

For grinding all steels, particularly well suited to difficult to machine materials such as **stainless steel**, **nickel alloys**, **chromium**, **titanium**, aluminium.

#### Note:

Other grit sizes, qualities, and dimensions are available on request in line with the manufacturer's minimum order quantities. Unless specified otherwise on the order, belts will be supplied with standard joints. See No. 568526ff for spare linishing belts for burnishing machines. Iron, sulphur and chlorine constituents: < 0.1 %

# **Technical description**

| Grit           | 80           |
|----------------|--------------|
| Grinding media | Ceramic grit |

| Grinding medium code                    | Ceramic        |
|---|----------------|
| Iron, sulphur and chlorine constituents | < 0.1 %        |
| Linishing belt width                    | 50 mm          |
| Linishing belt length                   | 3500 mm        |
| Product name attribute                  | 50×3500 mm     |
| Type of product                         | Linishing belt |