

# (A) linishing belt 237AA Trizact™, 50×2000 mm, Grit: 400



## **Order data**

Order number	558470 400
GTIN	2050001748003
Item class	53M

## **Description**

#### **Version:**

The **pyramid-shaped grit (A)** is based on an exactly aligned three-dimensional structure of very small Aluminium Oxide mineral particles. During the abrasive process new layers of grit particles are continuously exposed – right until the backing fabric (X fabric) is reached.

### **Application:**

For smoothing and finishing. For **absolutely consistent fine abrasive results** on all steels, chrome nickel steels, cobalt, nickel, and titanium alloys.

#### Note:

Other grit sizes, qualities, and dimensions are available on request in line with the manufacturer's minimum order quantities. Unless specified otherwise on the order, belts will be supplied with standard joints. See No. 568526ff for spare linishing belts for burnishing machines.

Iron, sulphur and chlorine constituents: < 0.1 %

3M grit designation: A45

## **Technical description**

Grit	400
3M grit designation	A45

Grinding medium code	Α
Iron, sulphur and chlorine constituents	< 0.1 %
Linishing belt width	50 mm
Linishing belt length	2000 mm
Product name attribute	50×2000 mm
Manufacturer's designation	237AA Trizact™
Type of product	Linishing belt