



## Rough grinding disc PREMIUM\*\*\* "2 in 1", Disc Ø×disc width: 230X4 mm



### Order data

Order number	560100 230X4
GTIN	9003170054065
Item class	53T

### Description

#### Version:

- **Grit, bonding, abrasive additives as well as reinforcement of the rough grinding discs are optimised for maximum metal removal rate and working life in their respective applications.**
- **Shapes: Rough grinding discs, depressed centres (shapes 27, 28, 29)**
- **Grinding angle 20° to 30°**
- **Application: On electric and pneumatic angle grinders with maximum 80 m/s circumferential speed for grinding welds, surfaces, and edges.**

Aggressive rough grinding disc (low hardness grade Q) for **universal use on stainless steel and steel** with high metal removal rate and long service life.

#### Specification: A30Q-BFX.

maximum circumferential speed: 80 m/s

Bore Ø: 22.23 mm

### Technical description

maximum speed	6600 rpm
Disc thickness	4 mm

Bore Ø	22.23 mm
Disc Ø	230 mm
Grinding medium code	A
Specification	A30Q-BFX
Iron, sulphur and chlorine constituents	< 0.1 %
recommended approach angle	20-30 degrees
optimised for material	Steel
optimised for material	INOX
maximum circumferential speed	80 m/s
Type of product	Rough grinding wheel