TROLD

Rough grinding disc PREMIUM*** Focur, Disc Ø×disc width: 125X7 mm



Order data

Order number	560200 125X7
GTIN	9003172337562
Item class	53T

Description

Version:

Special type for **grinding cast iron.** High-quality Zirconium Aluminium Oxide and Silicon Carbide permit very high metal removal rates at low contact forces, even on **castings with burnt-on residues.**

Specification: ZA24N-BFX.

- Grit, bonding, abrasive additives as well as reinforcement of the rough grinding discs are optimised for maximum metal removal rate and working life in their respective applications.
- · Shapes: Rough grinding discs, depressed centres (shapes 27, 28, 29)
- · Grinding angle 20° to 30°
- Application: On electric and pneumatic angle grinders with maximum 80 m/s circumferential speed for grinding welds, surfaces, and edges.

maximum circumferential speed: 80 m/s Bore Ø: 22.23 mm

Technical description

Disc thickness

7 mm

Bore Ø	22.23 mm
maximum speed	12200 rpm
Disc Ø	125 mm
Grinding medium code	ZA
Specification	A24Q-BFX
recommended approach angle	20-30 degrees
optimised for material	Cast iron
maximum circumferential speed	80 m/s
Type of product	Rough grinding wheel