

HOLEX
Rough grinding disc "2 in 1", Disc Ø×disc width: 150X6 mm

Order data

| | |
|--------------|---------------|
| Order number | 560500 150X6 |
| GTIN | 4045197802002 |
| Item class | 52M |

Description
Version:

- **Grit, bonding, abrasive additives as well as reinforcement of the rough grinding discs are optimised for maximum metal removal rate and working life in their respective applications.**
- **Shapes: Rough grinding discs, depressed centres (shapes 27, 28, 29)**
- **Grinding angle 20° to 30°**
- **Application: On electric and pneumatic angle grinders with maximum 80 m/s circumferential speed for grinding welds, surfaces, and edges.**

Rough grinding disc for **steel and stainless steel** with **long working life** and high metal removal rate.

Specification: A30Q-BF.

maximum circumferential speed: 80 m/s

Bore Ø: 22.23 mm

Technical description

| | |
|--------|----------|
| Disc Ø | 150 mm |
| Bore Ø | 22.23 mm |

| | |
|---|----------------------|
| Disc thickness | 6 mm |
| maximum speed | 10200 rpm |
| Grinding medium code | A |
| Specification | A30Q-BF |
| Iron, sulphur and chlorine constituents | < 0.1 % |
| recommended approach angle | 20-30 degrees |
| optimised for material | Steel |
| optimised for material | INOX |
| maximum circumferential speed | 80 m/s |
| Type of product | Rough grinding wheel |