



## Rough grinding disc PREMIUM\*\*\* RONDELLER®, 125 mm Ø, Grit: 60



### Order data

Order number	560920 60
GTIN	9003179082298
Item class	53T

### Description

#### Version:

- **Grit, bonding, abrasive additives as well as reinforcement of the rough grinding discs are optimised for maximum metal removal rate and working life in their respective applications.**
- **Shapes: Rough grinding discs, depressed centres (shapes 27, 28, 29)**
- **Grinding angle 20° to 30°**
- **Application: On electric and pneumatic angle grinders with maximum 80 m/s circumferential speed for grinding welds, surfaces, and edges.**

The patented grinding disc with high flexibility, cool grinding, very good chip removal, **smooth running** and **low noise emission**.

#### Application:

**Universal for steel, INOX (VA), cast iron, non-ferrous metals and thermo set plastics, for surface grinding and for working sheet metal parts and welds.**

Bore Ø: 22.23 mm

### Technical description

Grit	60
------	----

Bore Ø	22.23 mm
maximum speed	12200 rpm
Disc Ø	125 mm
Grinding medium code	A
Iron, sulphur and chlorine constituents	< 0.1 %
Product name attribute	125 mm Ø
recommended approach angle	20-30 degrees
optimised for material	INOX
optimised for material	Steel
optimised for material	Cast iron
optimised for material	INOX
maximum circumferential speed	80 m/s
Type of product	Rough grinding wheel