



## Cutting disc PREMIUM\*\*\*, Disc Ø: 230 mm



### Order data

Order number	563200 230
GTIN	9003178723437
Item class	53T

### Description

#### Version:

Aggressive cutting disc (low hardness grade Q) for **universal use on stainless steel and steel** with long service life and high stability.

#### Application:

For freehand cutting using electric and pneumatic angle grinders with maximum 80 m/s peripheral cutting speed  $v_c$ .

#### Specification:

##### A30Q-BFXA.

#### Note:

The disc thickness should be at least 20% of the material thickness to be cut.

maximum circumferential speed: 80 m/s

Shape description: flat

Bore Ø: 22.23 mm

Shape description: flat

Disc thickness: 2.5 mm

Bore Ø: 22.23 mm

### Technical description

Disc thickness	2.5 mm
Shape	41
maximum speed	6600 rpm
Bore Ø	22.23 mm
Shape description	flat
Specification	A30Q-BFXA
Disc Ø	230 mm
for material thicknesses	7.5 - 12.5 mm
Grinding medium code	A
Iron, sulphur and chlorine constituents	< 0.1 %
recommended approach angle	90 degrees
Propulsive equipment	Angle grinders
maximum circumferential speed	80 m/s
Type of product	Cutting-off wheel

---

## Accessories

Pair of clamping flanges Flange Ø 76 mm	563990 76
---	-----------