

Garant

CerRapid cutting disc EXTRA THIN, steel, STAINLESS, Disc Ø: 178 mm



Order data

Order number	563256 178
GTIN	4062406162337
Item class	51M

Description

Version:

Self-sharpening **ceramic grit (CER)** and the specially matched **high-performance binding system** enable **performance that is many times better, with extremely cool grinding** compared to conventional cutting discs (A).

- **Very high productivity thanks to very quick separating cuts.**
- **Optimum balance between extremely soft cutting behaviour with very low application force and very long working life.**

Specification:

CER60Q-BF.

Note:

The disc thickness should be at least 20% of the material thickness to be cut.

maximum circumferential speed: 80 m/s

Shape description: flat

Bore Ø: 22.23 mm

Shape description: flat

Disc thickness: 1.6 mm

Bore Ø: 22.23 mm

Technical description

Shape description	flat
Disc Ø	178 mm
Specification	CER60Q-BF
maximum speed	8600 rpm
Shape	41
Bore Ø	22.23 mm
Disc thickness	1.6 mm
Grinding medium code	Ceramic
Iron, sulphur and chlorine constituents	< 0.1 %
recommended approach angle	90 degrees
optimised for material	INOX
optimised for material	Steel
maximum circumferential speed	80 m/s
Type of product	Cutting-off wheel

Accessories

Pair of clamping flanges Flange Ø 76 mm	563990 76
---	-----------