



## Cutting disc CUBITRON™ II EXTRA THIN, Disc Ø: 125 mm



### Order data

Order number	563315 125
GTIN	5902658065040
Item class	53M

### Description

#### Version:

Extremely high cutting performance and long service life thanks to **Cubitron™ II precision ceramic grit.**

Very high practicality due to very soft, cutting action requiring only low force.

#### Application:

For very quick low-burr cutting with low thermal stress and easy ergonomic cut guidance.

For freehand cutting using electric and pneumatic angle grinders with maximum 80 m/s peripheral cutting speed  $v_c$ .

#### Specification:

##### A60S-BF.

#### Note:

The disc thickness should be at least 20% of the material thickness to be cut.

maximum circumferential speed: 80 m/s

Shape description: flat

Bore Ø: 22.23 mm

Shape description: flat

Disc thickness: 1 mm

Bore Ø: 22.23 mm

## Technical description

Disc Ø	125 mm
Bore Ø	22.23 mm
Shape description	flat
Disc thickness	1 mm
for material thicknesses	3 - 5 mm
Grinding media	Cubitron™ II
Grinding medium code	Ceramic
Iron, sulphur and chlorine constituents	< 0.1 %
recommended approach angle	90 degrees
Propulsive equipment	Angle grinders
maximum circumferential speed	80 m/s
Type of product	Cutting-off wheel