

Abrasive flap disc speed CER, flat, Ø 125 mm, Grit: 120



Order data

Order number	565235 120
GTIN	4062406159344
Item class	51M

Description

Version:

- · High-quality self-sharpening ceramic grit (CER) for maximum abrasive power and low contact pressure.
- Active coating for cool cutting.
- · Sturdy poly-cotton mixed fabric for ideal wear characteristics and stability, even when used on edges.
- Ergonomic and vibration-damping polyester plastic backing pad (can be reset).
- · Best results on high-power angle grinders.

speed - flat flap strip arrangement, for **high metal removal rate** and long tool life.

Application:

Precise chamfering, edge smoothing and surface abrasion.

maximum circumferential speed: 80 m/s

Shape description: flat

Bore Ø: 22.23 mm

Technical description

Disc Ø	125 mm
	· — · · · · · · · · · · · · · · · · · ·

Grit	120
Shape description	flat
Bore Ø	22.23 mm
Grinding media	Ceramic grit (CER)
Grinding medium code	Ceramic
abrasive, cooling coating	yes
Iron, sulphur and chlorine constituents	< 0.1 %
Product name attribute	Ø 125 mm
optimised for material	INOX
maximum circumferential speed	80 m/s
Type of product	Abrasive flap disc