

Garant

Abrasive flap disc speed CER, flat, Ø 125 mm, Grit: 40



Order data

| | |
|--------------|---------------|
| Order number | 565235 40 |
| GTIN | 4062406159313 |
| Item class | 51M |

Description

Version:

- **High-quality self-sharpening ceramic grit (CER) for maximum abrasive power and low contact pressure.**
- **Active coating for cool cutting.**
- **Sturdy poly-cotton mixed fabric for ideal wear characteristics and stability, even when used on edges.**
- **Ergonomic and vibration-damping polyester plastic backing pad (can be reset).**
- **Best results on high-power angle grinders.**

speed - flat flap strip arrangement, for **high metal removal rate** and long tool life.

Application:

Precise chamfering, edge smoothing and surface abrasion.

maximum circumferential speed: 80 m/s

Shape description: flat

Bore Ø: 22.23 mm

Technical description

| | |
|-------------------|------|
| Shape description | flat |
|-------------------|------|

| | |
|---|--------------------|
| Grit | 40 |
| Disc Ø | 125 mm |
| Bore Ø | 22.23 mm |
| Grinding media | Ceramic grit (CER) |
| Grinding medium code | Ceramic |
| abrasive, cooling coating | yes |
| Iron, sulphur and chlorine constituents | < 0.1 % |
| Product name attribute | Ø 125 mm |
| optimised for material | INOX |
| maximum circumferential speed | 80 m/s |
| Type of product | Abrasive flap disc |