


**969F flap disc Cubitron™ II, glass fibre pad flat, Ø 125 mm, Grit: 40**

**Order data**

|              |               |
|--------------|---------------|
| Order number | 565496 40     |
| GTIN         | 4054596197046 |
| Item class   | 53F           |

**Description**
**Version:**

Coated with **precisely formed Cubitron™ II** ceramic grit for **maximum metal removal rate and working life**.

Ideal for edge grinding.

**Application:**

Ideal for **quick** and **cool grinding** of difficult-to-machine steels using high-powered angle grinders.

maximum circumferential speed: 80 m/s

Shape description: flat

Bore Ø: 22.23 mm

**Technical description**

|                   |                    |
|-------------------|--------------------|
| Shape description | flat               |
| Grit              | 40                 |
| Bore Ø            | 22.23 mm           |
| Grinding media    | Ceramic grit (CER) |

|   |                    |
|---|--------------------|
| Grinding medium code                    | Ceramic            |
| Iron, sulphur and chlorine constituents | < 0.1 %            |
| Product name attribute                  | Ø 125 mm           |
| optimised for material                  | Steel              |
| optimised for material                  | INOX               |
| maximum circumferential speed           | 80 m/s             |
| Type of product                         | Abrasive flap disc |